



# Series variation



# High power cylinder SHC Series

- LCM
- LCR
- LCG
- LCW
- LCX
- STM
- STG
- STS/STL
- STR2
- UCA2
- ULK\*
- JSK/M2
- JSG
- JSC3/JSC4
- USSD
- UFCD
- USC
- UB
- JSB3
- LMB
- LML
- HCM
- HCA
- LBC
- CAC4
- UCAC2
- CAC-N
- UCAC-N
- RCS2
- RCC2
- PCC
- SHC**
- MCP
- GLC
- MFC
- BBS
- RRC
- GRC
- RV3\*
- NHS
- HRL
- LN
- Hand
- Chuk
- MecHnd/Chuk
- ShkAbs
- FJ
- FK
- SpdContr
- Ending

Variation	Model No. JIS symbol	Bore size (mm)	Standard stroke (mm)												Min. stroke (mm)	Max. stroke (mm)	Custom stroke (per mm)	Booster stroke (mm)				Mounting	
																				Basic	Axial foot		
			100	150	200	250	300	350	400	500	600	700	800	900				1000	10			20	00
Double acting/double force 	SHC	ø40/ø50	●	●	●	●	●	●	●	●	●	●	●	●	700	●	●	●	●				
		ø63	●	●	●	●	●	●	●	●	●	●	●	●	800	●	●	●	●				
		ø80	●	●	●	●	●	●	●	●	●	●	●	●	900	●	●	●	●				
		ø100	●	●	●	●	●	●	●	●	●	●	●	●	1000	●	●	●	●				
Double acting/quad force 	SHC-K	ø40/ø50	●	●	●	●	●	●	●	●	●	●	●	700	●	●	●	●					
		ø63	●	●	●	●	●	●	●	●	●	●	●	800	●	●	●	●					
		ø80	●	●	●	●	●	●	●	●	●	●	●	900	●	●	●	●					
		ø100	●	●	●	●	●	●	●	●	●	●	●	1000	●	●	●	●					

